



Address:
JAMBU PERSHAD & SONS
6275/22 Nicholson Road,
Ambala Cantt, Haryana,
INDIA
Pin: 133001

Email:
sales@japson.com
japsonambala@yahoo.com

Website:
www.japson.com
Phone:
+91-171-4006897

Automatic Water Distillation Equipment (Cabinet Model), Borosilicate Glass

Product Image



Description

This is a fully automatic water distillation equipment and can be used in research laboratories, hospitals etc. It is manufactured from 3.3 borosilicate glass. The distillation has following features :

Replaceable Silica Sheathed (Quartz) Heater : The horizontal jacket is fitted with removable silica sheathed heater and screw threaded connectors for ease of cleaning.

Distillate temperature is approx. between 25^o to 45^o C which is ensured by an efficient condenser.

The stand is powder coated for rust free operation and lustrous appearance.

Cooling water from the condenser is re-circulated into the boiling chamber, hence saving energy.

Screw Threaded Connectors : These are provided for easy plumbing & Installation to avoid any glassware breakage during assembly.

Fuse is provided for safety in case of voltage fluctuation or short circuit.

Boiler is provided with Replaceable Constant Level Device for easy draining and cleaning of boiling chamber.

The front cover is easily removable making the access to the glass parts very easy.

Additional built-In Safety Features :

Gate Valve : Conserves cooling water wastage in case of power failure.

Flow Switch : In-built safety feature for the equipment unit shut off in case of cooling water failure.

Temperature Switch : The boiler is equipped with a safety temperature switch which shuts off the unit if water level in the boiler falls below the heater, thus saving the glass parts from any damages.

Level Sensor : It shuts off the distillation equipment if the water level in the boiler falls below the heater.

Reservoir Level Sensor : This helps in automatic working of the water distillation equipment. Depending on the water level in the reservoir it will automatically switch On/Off the equipment, thus saving energy. (Reservoir can also be provided with a storage capacity of 5 litre, 10 litre & 20 litre made of Borosilicate Glass or polypropylene.

Particulars

Catalog No.

Automatic Water Distillation Equipment (Cabinet Model),
Borosilicate Glass, Output Capacity: 2 Litre/Hour, Single Stage, pH:
5.5-6.0, Conductivity uS/cm: 1.0-2.0, Cooling Water Requirement
(Approx): 1.5 litre/Minute, Power Rating (total): 1.5KW

JA23630

Automatic Water Distillation Equipment (Cabinet Model),
Borosilicate Glass, Output Capacity: 2 Litre/Hour, Double Stage, pH:
6.0-7.0, Conductivity uS/cm: 0.8-1.0, Cooling Water Requirement
(Approx): 2.0 litre/Minute, Power Rating (total): 3.0KW JA23631

Automatic Water Distillation Equipment (Cabinet Model),
Borosilicate Glass, Output Capacity: 4 Litre/Hour, Single Stage, pH:
5.5-6.0, Conductivity uS/cm: 1.0-2.0, Cooling Water Requirement
(Approx): 2-3 litre/Minute, Power Rating (total): 3.0KW JA23632

Automatic Water Distillation Equipment (Cabinet Model),
Borosilicate Glass, Output Capacity: 4 Litre/Hour, Double Stage, pH:
6.0-7.0, Conductivity uS/cm: 0.8-1.0, Cooling Water Requirement
(Approx): 2-4 litre/Minute, Power Rating (total): 6.0KW JA23633

Disclaimer

The Products details given on this page are indicative in nature and JAPSON reserves the right to change them without prior notice. Buyer is also requested to re-check the specifications and other features of product at the time of order as product development is a continuous process and minor modifications may be made to design based on latest availability, process and design.