Address:
JAMBU PERSHAD & SONS
6275/22 Nicholson Road,
Ambala Cantt, Haryana,
INDIA
Pin: 133001

Email:
sales@japson.com
japsonambala@yahoo.com

Website:
www.japson.com
Phone:
+91-171-4006897

BOD Incubator, Aluminium with PID Controller

Product Image

Description

B.O.D. Incubators are suitable for preservation of vaccines, insulin, lever extracts, chemicals etc. and to make biochemical oxygen demand determination.
Construction : The low temperature incubator is made of double walled M.S. sheet finished with epoxy based powder coated paint. Inner chamber is made of anodized aluminium. Two doors are provided. Inner door is made of transparent acrylic for inspecting specimens outer door is insulated and is fitted with magnetic tape with lock and key. Temperature range from 5° c to 50° c with an accuracy of ± 1° c provided with two air circulating fans, high performance compressor, cooling coils, heating elements, P.I.D. based temperature control and display. It is fitted with a door operated illumination and a caster wheel for easy mobility.

Particulars	Catalog No.
BOD Incubator, Aluminium with PID Controller, 825x505x415mm, 6.1 Cubic Feet	JA22240
BOD Incubator, Aluminium with PID Controller, 850x600x500mm, 8 Cubic Feet	JA22241
BOD Incubator, Aluminium with PID Controller, 880x550x550mm, 10 Cubic Feet	JA22242
BOD Incubator, Aluminium with PID Controller, 900x650x580mm, 12 Cubic Feet	JA22243

Note: Custom-made incubators to your specific requirements like size, material, control mechanism, configuration, shelves or special needs available on demand.

Disclaimer