



Address:
JAMBU PERSHAD & SONS
6275/22 Nicholson Road,
Ambala Cantt, Haryana,
INDIA
Pin: 133001

Email:
sales@japson.com
japsonambala@yahoo.com

Website:
www.japson.com
Phone:
+91-171-4006897

Centrifuge, Laboratory, High Speed, 10000 R.P.M.

Product Image



Description

Model : 10M

Specifications:

- Bench Top High Speed Centrifuge Machine.
- Microprocessor based with digital timer 0 -59 minutes.
- Heavy duty C.R.C. construction finished with powder coating.
- Metallic centrifugal bowl for extra protection and easy cleaning.
- Fitted with well balanced universal motor (with carbons).
- 2 lines of 16 character LCD display of r.p.m., Set time and run time.
- Programmable Speed controller from 2000 to 10000 in variation of 100 r.p.m.
- Last test parameter recall and displays automatically on LCD.
- Lid lock for safe drive.
- Rotors made of Aluminium Alloy to withstand high speed of 10000 r.p.m.

Technical Parameter

• Max. Speed	10000 r.p.m.
• Motor	Universal Motor (With carbon)
• Power	AC 220V 50 Hz \pm 10%
• Dimensions	510 x 510 x 390mm
• Weight of Machine	21 kg approx.,
• Dimension & wt. with Box	23.5 kg

Machine comes with only one rotor which can be selected from below mentioned table.

Rotor Type	Rotor Capacity	Max. Speed on Rotor (r.p.m.)
▶ Angle Head	12 x 1.5/2ml	10000
▶ Angle Head	24 x 1.5/2ml	10000
▶ Angle Rotor	8 x 5 ml	10000
▶ Angle Rotor	8 x 15 ml	10000
▶ Angle Head	4 x 25ml	10000
▶ Angle Rotor	4 x 50 ml	10000

Note:

This is our general purpose leaflet. We can amend technical features according to the requirement of customer but with prior consent on our letter head.

-

Centrifuge, Laboratory, High Speed, 10000 R.P.M.

Catalog No. 100749

Disclaimer

The Products details given on this page are indicative in nature and JAPSON reserves the right to change them without prior notice. Buyer is also requested to re-check the specifications and other features of product at the time of order as product development is a continuous process and minor modifications may be made to design based on latest availability, process and design.