

Address: JAMBU PERSHAD & SONS 6275/22 Nicholson Road, Ambala Cantt, Haryana, INDIA Pin: 133001 **Email:** sales@japson.com japsonambala@yahoo.com **Website:** www.japson.com **Phone:** +91-171-4006897

# **HPLC System**

# **Product Image**



#### Description

Catalog No: 100141

High-Pressure Liquid Chromatograph - Model 3201

#### **MEASUREMENT RANGE**

- Parameters Measurement range
- > WBC (0-99.9×109)/L
- > RBC (0-9.99×1012)/L
- ➢ HGB (0-300.0)g/L
- > PLT (0-999×109)/L

## **TECHNICAL SPECIFICATIONS**

- Principle Impedance for cell countingCyanide-free method for HGB
- ✓ Parameters WBC, Neu#, Lym#, Mid#, Neu%,Lym%, Mid%, RBC, HGB, HCT, MCV, MCH, MCHC,RDW-SD, RDW-CV, PLT, MPV, PDW, PCT, P-LCR
- ✓ Histograms WBC, RBC, PLT histogram
- ✓ Languages English, Spanish, Italian, Portuguese, etc.
- ✓ Calibration Manual and Auto-calibration
- Quality control
  3 level QC, LJ graph
- ✓ Sample volume Venous mode: 10ìL venous blood Capillary mode:
  - 10ìL capillary blood Prediluted mode: 20ìL capillary blood
- ✓ Display 8-inch color touch screen Liquid Crystal Display (LCD)
- ✓ Resolution 800 600
- ✓ Storage 100,000 sample results with histograms
- ✓ Reagent Lyse(500mL) and Diluent(20L)
- Printout Thermal printer, support external printer
- ✓ Temperature 18 35°C
- ✓ Power AC 100-240V, 50/60±1Hz
- ✓ Dimension 410mm×435mm×472mm

# SALIENT FEATURES

- ✓ Throughput: 35T/H 8-inch touch screen 20 parameters + 3 histograms Sample volume: 10 µL
- ✓ Reagents only
- ✓ Counting modes
- ✓ 100,000 sample results
- Support LIS and external printer
- ✓ CE marked
- ×

## Disclaimer

The Products details given on this page are indicative in nature and JAPSON reserves the right to change them without prior notice. Buyer is also requested to re-check the specifications and other features of product at the time of order as product development is a continuous process and minor modifications may be made to design based on latest availability, process and design.