



Address:
JAMBU PERSHAD & SONS
6275/22 Nicholson Road,
Ambala Cantt, Haryana,
INDIA
Pin: 133001

Email:
sales@japson.com
japsonambala@yahoo.com

Website:
www.japson.com
Phone:
+91-171-4006897

Water Deionization Apparatus

Product Image



Description

Laboratory Water Deionizer is used to produce conductivity de mineralized water and to

bring down the dissolved solid to less than 1mg/lit. For deionization both cation and anion resins are kept in the same column of Portable Water Deionizer and are intimately mixed together during the treatment. So the unit consists of single column, conductivity meter, with all control of valves. De-ionized water will have the conductivity of less than 1 ms/cm and pH of 6.8 to 7.

Widely Used to:

Produce conductivity de mineralized water.

Bring down the dissolved solid to less than 1mg /lit.

Applications :

Research laboratories

Pharmaceutical industries

Scientific institutions

Medical institutes

Microbiology laboratories

Output Range:

50 Litres/Hour

90 Litres/Hour

100 Litres/Hour

-

Water Deionization Apparatus, 50 Litres/Hour

Catalog No. 100703 (A)

Water Deionization Apparatus, 90 Litres/Hour

Catalog No. 100703 (B)

Water Deionization Apparatus, 100 Litres/Hour

Catalog No. 100703 (C)

Disclaimer

The Products details given on this page are indicative in nature and JAPSON reserves the right to change them without prior notice. Buyer is also requested to re-check the specifications and other features of product at the time of order as product development is a continuous process and minor modifications may be made to design based on latest availability, process and design.